

DAV PUBLIC SCHOOL, ETWA NAGAR, BEGUSARAI
BOQ for Renovation of Conference Hall

SL.NO		DESCRIPTION	UNIT	QTY.	RATE	AMOUNT
1	Derived from 15.23.1	Chipping of whole floor area except toilets for preparing the floor surfaces rough, clean and usable for new floor tiles pasting.	Sqm	167.03		
2	11.41	Providing and laying vitrified floor tiles in different sizes {thickness to be specified by the manufactruer) with water absorption's less than 0.08 % and conforming to IS : 15622 of approved make in all colours and shades, laid on 20 mm thick cement mortar 1:4 (1 cement: 4 coarse sand) including grouting the joint with white cement and matching pigments etc., complete. (STAFF ROOM)				
	11.41.1	Size of Tile 60x60 cm	Sqm	167.03		
3	11.46	Providing and laying Vitrified tiles in different sizes (thickness to be specified by manufacturer), with water absorption less than 0.08 % and conforming to I.S. 15622, of approved make, in all colours & shade, in skirting, riser of steps, over 12 mm thick bed of cement mortar 1:3 (1 cement: 3 coarse sand), including grouting the joint with white cement & matching pigments etc. complete.				
	11.46.2	Size of Tile 600 x 600 mm.	Sqm	8.45		
4	15.23	Dismantling tile work in floors and roofs laid in cement mortar including stacking material within 50 metres lead.				
	15.23.1	For thickness of tiles 10 mm to 25 mm	Sqm	32.58		
5	13.74	Removing white or colour wash by scrapping and sand paper in and preparing the surface smooth including necessary repair scratches etc. complete	Sqm	316.61		
6	13.80A.2	Providing and applying white cement based putty of average thickness 2 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	Sqm	316.61		
7	13.92	Wall painting with plastic emulsion paint of approved brand and manufacture to give an even shade:				
	13.92.1	Two or more coats on new work	Sqm	316.61		
8	21.1	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / aneling.C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) :				
	21.1.1	For fixed portion				

DAV PUBLIC SCHOOL, ETWA NAGAR, BEGUSARAI
BOQ for Renovation of Conference Hall

	21.1.1.1	Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)	Kg	238.50		
9	21.1.2	For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately)				
	21.1.2.1	Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)	Kg	119.25		
10	21.3	Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge . (Cost of aluminium snap beading shall be paid in basic item):				
	21.3.2	With float glass panes of 5.50 mm thickness(weight not less than 12.50 kg/sqm)	Sqm	34.35		
11	21.8	Filling the gap in between aluminium frame & adjacent RCC/Brick/Stone work by providing weather silicon sealant over backer rod of approved quality as per architectural drawings and direction of Engineer-in-charge complete.				
	21.8.1	Upto 5mm depth and 5 mm width	Metre	87.17		
12		12mm toughened glass door with Dorma fittings Inclusive of: • 12mm toughened glass, Clear • Dorma patch fittings, WCP, & handles (as attached) • Dowsil silicone, 688 • Installation • Handling & transportation • GST	Each	1		
		Door Size:5'0" x 8'-0" = 40.00 S.Ft (3.71 Sqm)				
		TOTAL				
		Note:-				
	1)	Rate inclusive of GST				